



547067

(43) International Publication Date
10 September 2004 (10.09.2004)


PCT

(10) International Publication Number
WO 2004/075996 A2

- (51) International Patent Classification⁷: **A63B**
- (21) International Application Number:
PCT/IB2004/000607
- (22) International Filing Date: 27 February 2004 (27.02.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
BG2003A000016 28 February 2003 (28.02.2003) IT
- (71) Applicant (for all designated States except US): **PRINCE SPORTS, INC.** [US/US]; One Advantage Court, Bordentown, NJ 08505 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **PEZZATO, Mauro** [IT/IT]; Via K2, 11, I-31100 Treviso (IT). **POZZOBON, Michele** [IT/IT]; Via Fiume, 10, I-31050 Fossalonga di Veduggio (IT).
- (74) Agents: **ZANOLI, Enrico et al.**; Zanoli & Giavarini, S.r.l., Viale Bianca Maria, 35, I-20122 Milano (IT).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Declaration under Rule 4.17:**
— of inventorship (Rule 4.17(iv)) for US only
- Published:**
— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: SPORTS RACQUET WITH FRAME OPENINGS



(57) Abstract: A sports racquet has a plurality of opposed string holes for anchoring the ends of the strings. at least one pair of contiguous string holes are replaced with an enlarged string hole having opposed bearing surfaces for securing the ends of a pair of contiguous string segments. Preferably, a plurality of contiguous enlarged string holes are employed along the sides, tip, and heel or throat bridge of the racquet, in order to reduce the weight of the racquet head. Also, preferably, the enlarged string holes are defined by a pair of opposed interior walls of the frame extending between the frame's inner and outer surfaces, thereby forming a truss-like internal structure for stiffening the frame. Moreover, the frame preferably has interior wall portions that extend between the string holes. Such wall portions lie in the string bed plane and underlie the string portions on the exterior of the frame.

WO 2004/075996 A2



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.